

**X62 - COPPER CYANIDE ELECTROPLATING, CHEMICAL FUME SUPPRESSANT CONTROLLED**

**CALCULATION METHODS**

$E_a = U_a \times EF$

$E_h = U_h \times EF$

**NOTES:**

-  $U_a$  = Annual electrical usage, ampere-hour/year

-  $U_h$  = Maximum hourly electrical usage, ampere-hour/ hour

- Assume 95% control efficiency for anti-mist additives (i.e. foam, fume suppressant). See ARB Tech. Support Doc. to Proposed ATCM for Emissions of Cr+6 from Chrome Plating & Chromic Acid Anodizing Operations

(Jan. 1988), Table III-2 and ARB Tech. Guidance Doc. to the Criteria & Guidelines Reg. for AB2588 (Aug. 1989), page 44.

- Assume TSP = PM-10.

-  $C_i$  = Weight percent of other listed substance in solution, %.

-  $C_{CN}$  = Weight percent of cyanide in solution, %.

- "OTHER" pollutants and their corresponding emission factors are to be manually entered.

- Assume 100% capture efficiency.

POLLUTANT	Emission Factor	REFERENCE	ARB	(UNITS)	COMMENTS
	(lbs/amp-hr)	DOCUMENT	FACTOR		
NOX					
CO					
SOX					
TOG					
ROG					
TSP	4.29E-09	Default TSP/PM-10 EF = CN + Cu EF's = 4.29E-9 lbs/amp-hr.			
PM10	4.29E-09	Assume that TSP and PM-10 are based on average weight percent of cyanide in solution.			
ALUMINUM					
BERYLLIUM					
CADMIUM					
CHLORINE					
CYANIDE	1.93E-09	AP-42 (July 1996), Table 12.20-4 = 2.7E-6 grains CN/dscf -> 2.7E-4 grains CN/amp-hr.			
COPPER	2.36E-09	Copper EF determined using CN EF and ratio of Cu in $Cu(CN)_2 = 1.93E-9 \times [63.5/(26)(2)]$			
OTHER	1.93E-9 x Ci/C CN				