

DRAFT

San Diego County Air Pollution Control District

10124 Old Grove Rd
San Diego, CA 92131-1649
(858) 586-2600

TITLE V OPERATING PERMIT APCD2009-PTO-974746

Issued To:

Neo San Diego LLC
Site ID # APCD1996-SITE-09779

Site Address

5244 Convoy Street
San Diego, CA 92111
(949) 355-5182

Mailing Address

5087 Junction Road
Lockport, NY 14094

Responsible Official – Anthony J. Falbo

Facility Contact – John Hickzewski

Permit Information Contact – Suparna Chakladar

Issued by the San Diego County Air Pollution Control District on

This Title V Operating Permit expires on

Signed by: _____
ROBERT J. KARD, Air Pollution Control Officer

Date: _____

TABLE OF CONTENTS

	PAGE
PREAMBLE	1
SECTION I. REGULATION XIV PERMIT REQUIREMENTS	2
A. ADMINISTRATIVE PERMIT TERMS	2
B. RENEWAL REQUIREMENTS AND TERMS	2
C. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS	3
D. GENERAL PERMIT REQUIREMENTS	4
SECTION II. FACILITY-WIDE REQUIREMENTS	5
A. GENERAL PERMIT PROGRAM APPLICABLE REQUIREMENTS	5
B. GENERAL PROHIBITORY APPLICABLE REQUIREMENTS	5
C. PERMIT SHIELDS	6
D. ADDITIONAL TERMS	6
SECTION III. EMISSION UNIT REQUIREMENTS	6
A. DISTRICT PERMITTED EMISSION UNITS	6
B. REGISTERED AND LEASED EMISSION UNITS	6
C. INSIGNIFICANT EMISSION UNITS AND ACTIVITIES	7
D. ENGINES SUBJECT TO THE FEDERAL NESHAP	7
SECTION IV. DISTRICT ONLY PROVISIONS	7
A. VARIANCE PROCEDURES	7
SECTION V. APPENDICES	A-1
A. DISTRICT PERMITS AND REGISTERED UNITS	A-1
B. RULE REFERENCE TABLE	B-1
C. ABBREVIATIONS	C-1

PREAMBLE

This Title V Operating Permit consists of this document and all appendices, including District permits incorporated by reference. The facility is subject to all applicable requirements identified within this permit, unless a specific permit shield is specified within this permit. If an applicable requirement is omitted from this permit, the facility is still obligated to comply with such an applicable requirement. The permittee must comply with all of the terms listed in each section of this permit.

This permit contains five major sections: Section I contains the Regulation XIV requirements required to carry out the Title V Operating Permit program. Section II contains the requirements that are applicable to the facility on a facility-wide basis. Section III contains the requirements that are applicable to individual emission units which have been issued District permits or District registration, or which have been determined to be insignificant emission units. Section IV contains terms and requirements pertaining to variance procedures and compliance schedules, if applicable to the facility. Section V contains three appendices. Appendix A contains all the District permits incorporated within this permit. Appendix B contains a table of all SIP approved and District approved rules. Appendix C contains a list of abbreviations used within this permit.

Copies of the Rules and Regulations of the Air Pollution Control District of San Diego County and the Rules and Regulations for San Diego County contained in the State Implementation Plan (SIP) approved by EPA may be obtained at the District. Copies are also available for review at the following locations:

SD Air Pollution Control District (Library & Public Review Area)	County of SD Law Library (Downtown)	County of SD Law Library (North County)
10124 Old Grove Rd	1105 Front St.	325 S. Melrose Suite 300
San Diego, CA 92131-1649	San Diego, CA 92101	Vista, CA 92083
(858) 586-2600	(619) 531-3900	(760) 940-4386

The current Rules and Regulations of the Air Pollution Control District of San Diego County may also be viewed and downloaded using the following internet address:

www.sdapcd.org

The following addresses should be used to submit any certifications, reports or other information required by this permit:

SD Air Pollution Control District Compliance Division 10124 Old Grove Rd San Diego, CA 92131-1649	USEPA Region IX Director of the Air Division Attn: Air-3 75 Hawthorne Street San Francisco, CA 94105
--	---

SECTION I. REGULATION XIV PERMIT REQUIREMENTS

A. ADMINISTRATIVE PERMIT TERMS

1. This Title V Operating Permit expires 5 years from date of issuance. [Rule 1410]
2. Commencing or continuing operation under this permit to operate shall be deemed acceptance of all terms and conditions specified within this permit. This does not limit the right of the applicant to seek judicial review or seek federal EPA review of a permit term or condition. [Rule 1421]
3. This permit may be modified, revoked, reopened and reissued, or terminated by the District for cause. [Rule 1421]
4. The filing of a request by the facility for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay the applicability of any permit condition. [Rule 1421]
5. This permit does not convey any property rights of any sort, or any exclusive privilege. [Rule 1421]
6. The need for the permittee to halt or reduce a permitted activity in order to maintain compliance with any term or condition of this permit shall not be a defense for any enforcement action brought as a result of a violation of any such term or condition. [Rule 1421]
7. In the event of challenge to any portion of this permit, the rest of the permit remains valid. [Rule 1421]
8. For the purpose of submitting compliance certifications or establishing whether or not a person has violated or is in violation of any applicable requirement in this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information, relevant to whether a source would have been in compliance with applicable requirements if the appropriate performance or compliance test or procedure had been performed. [62 Federal Register 8314; Rule 1421]

B. RENEWAL REQUIREMENTS AND TERMS

1. The permittee shall submit a complete application for renewal of this permit to the Air Pollution Control Officer at least 12 months, but not more than 18 months, prior to permit expiration. [Rule 1410]
2. If an administratively complete application for renewal of this permit has been submitted to the Air Pollution Control Officer within the timeframe specified in Section I.B.1. , the terms and conditions of this permit shall remain in effect and the source may continue operations under these terms and conditions until the Air Pollution Control Officer issues or denies the permit renewal. [Rule 1410]

C. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS

1. The permittee shall provide the District access to the facility and all equipment subject to this permit, and access to all required records pursuant to California Health and Safety Code Section 41510. [Rule 1421]
2. The permittee shall maintain all records required by this permit including any calibration, maintenance, and other supporting information and copies of all reports required by this permit for at least five years from their date of creation. Such records shall be maintained on-site for a minimum of three years. [Rule 1421]
3. The permittee shall submit monitoring and recordkeeping summary reports and all other monitoring and recordkeeping reports required by this permit to the District every six months, unless a shorter time frame is required by a specific permit condition contained in Section III of this permit. Unless other dates are specified in Section III, reports for data required to be collected from January 1 through June 30, shall be submitted no later than September 1 of the calendar year, and reports for data required to be collected from July 1 through December 31, shall be submitted no later than March 1 of the following calendar year. The report for the final six months of the year may be consolidated with the annual compliance certification required below. All instances of noncompliance from federally enforceable applicable requirements shall be clearly identified in these reports. (Timely completion of District Certification Reports Form J1 and Form J2, if applicable, and all indicated attachments, fulfills the requirements of this condition.) [Rule 1421]
4. Each calendar year, the permittee shall submit to the District and to the federal EPA an annual compliance certification, in a manner and form approved in writing by the District, for the previous calendar year that includes the identification of each applicable term or condition of the final permit for which the compliance status is being certified, the compliance status and whether the facility was in continuous or intermittent compliance during the previous calendar year, identification of the method used to determine compliance during the previous calendar year, and any other information required by the District to determine the compliance status. The annual compliance certification for a calendar year shall be submitted no later than March 1 of the following calendar year and may be consolidated with the monitoring and recordkeeping report for the last six months of the year for which compliance is certified. (Timely completion of District Certification Reports Form J1 and Form J2, if applicable, and all indicated attachments, fulfills the requirements of this condition.) [Rule 1421]
5. Any report submitted to the District or federal EPA pursuant to this permit to comply with a federally enforceable applicable requirement, shall be certified by a responsible official stating that, based on information and belief formed after reasonable inquiry, the report is true, accurate and complete. [Rule 1421]
6. The permittee shall make any trade secret designations of records, documents, or other information submitted to the District or federal EPA in accordance with District Rule 176. [Rule 176]
7. The permittee shall report all deviations from any and all federally enforceable permit terms and conditions including: (a) breakdowns, whether or not they result in excess emissions, (b)

deviations that result in excess emissions of any regulated air pollutant, and (c) deviations from monitoring, recordkeeping, reporting and other administrative requirements that do not result in excess emissions. For deviations that result from breakdowns under District Rule 98, the permittee shall report the breakdown within two hours of detection of the breakdown and provide a follow-up written report after corrective actions have been taken. For deviations not due to a breakdown but which result in excess emissions, the permittee shall report the deviation within ten calendar days of detection. For all other deviations where no specific time frame for reporting a deviation applies, the permittee shall report the deviation at the time of the next semi-annual monitoring summary or annual compliance certification, whichever occurs first. If an underlying applicable requirement contains a definition of prompt or otherwise specifies a time frame for reporting deviations, then the criteria for the applicable requirement shall apply. The report must include the probable cause of such deviations and any corrective actions or preventive measures taken. [Rule 1421]

D. GENERAL PERMIT REQUIREMENTS

1. The permittee shall comply with all terms and conditions of this permit. This permit consists of this document and Appendices A, B and C. Any noncompliance with the federally applicable terms and conditions of this permit shall constitute a violation of the federal Clean Air Act. Noncompliance with any federally applicable permit term or condition of this permit is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. Noncompliance with any District permit term or condition is grounds for enforcement action by the District. [Rule 1421]
2. Upon a written request by the District, the permittee shall furnish to the District any information needed to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit; any information required to determine compliance with this permit; or any records required to be maintained pursuant to this permit. Such information shall be provided within a reasonable time, as specified within the District's written request. [Rule 1421]
3. The permittee shall pay annual fees in accordance with District Rule 40. [Rule 1421]
4. The permittee shall provide access, facilities, utilities and any necessary safety equipment for source testing and inspection upon request from the District. [Rule 19]
5. This permit shall be maintained on-site at all times and be made available to the District upon request. [Rule 1410]
6. The permittee shall only make changes to its operations as allow by this permit and that comply with the requirements for permit amendments, modifications and other changes as given in Rules 1410 and 10. [Rules 1410(i) through (o) and (q); Rule 10]
7. The Rule Reference Table provided in Appendix B shall be used to determine whether a cited rule is a federally and District enforceable requirement or a District only enforceable requirement. Any new or revised District rule shall not be considered federally enforceable until the rule is approved by EPA into the SIP. In cases where SIP approval is pending for a revised District rule, the rule citation shall refer to both the current SIP approved rule and the revised District rule. [Rule 1421]

SECTION II. FACILITY-WIDE REQUIREMENTS

SECTION II. FACILITY-WIDE REQUIREMENTS

A. GENERAL PERMIT PROGRAM APPLICABLE REQUIREMENTS

The permittee shall comply with the applicable requirements specified in the following rules and regulations cited below, unless specifically exempted by the same rule or regulation.

Regulation	Rule Citation	Title
SDCAPCD Reg. II	10	Permits Required
SDCAPCD Reg. II	19	Provision of Sampling & Testing Facilities
SDCAPCD Reg. II	19.3	Emission Information
SDCAPCD Reg. II	21	Permit Conditions
SDCAPCD Reg. IV	60	Circumvention
SDCAPCD Reg. VI	101	Burning Control
SDCAPCD Reg. VIII	126	SD County Emergency Plan - Applicability
SDCAPCD Reg. VIII	131	Stationary Source Curtailment Plan
SDCAPCD Reg. VIII	132	Traffic Abatement Plan

B. GENERAL PROHIBITORY REQUIREMENTS

The permittee shall comply with the generally applicable requirements specified in the Rules and Regulations cited below, unless specifically exempted by the same Rule or Regulation. These generally applicable requirements apply on a facility-wide basis to all permitted equipment, registered equipment, and insignificant activities. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more permitted emission units, the requirement is also included in Section III.A. of this permit.

Regulation	Rule Citation	Title
SDCAPCD Reg. IV	50	Visible Emissions
SDCAPCD Reg. IV	51	Nuisance
SDCAPCD Reg. IV	67.0	Architectural Coatings
SDCAPCD Reg. IV	67.17	Storage of Materials Containing VOC
SDCAPCD Reg. IV	71	Abrasive Blasting
SDCAPCD Reg. VI	102	Open Fires – Western Section
SDCAPCD Reg. VI	105	Burning Permits
SDCAPCD Reg. VI	106	Permit Duration
SDCAPCD Reg. VI	107	Burning Hours
SDCAPCD Reg. VI	108	Burning Conditions
SDCAPCD Reg. VI	111	Prior Notification
SDCAPCD Reg. VI	112	Burning Report
SDCAPCD Reg. X	Subpart A	NSPS - General Provisions
SDCAPCD Reg. XI	Subpart A	NESHAP - General Provisions

SDCAPCD Reg. XI	Subpart M, 361.145	NESHAP - Standard for Demolition and Renovation
SDCAPCD Reg. XI	Subpart M, 361.150	NESHAP - Standard for Waste Disposal for Manufacturing, Fabricating, Demolition, Renovation, and Spraying Operations
40 CFR Part 82	Subpart A	Production and Consumption Controls
40 CFR Part 82	Subpart B	Servicing of Motor Vehicle Air Conditioners
40 CFR Part 82	Subpart F	Recycling and Emissions Reduction

C. ADDITIONAL TERMS

1. Any emission unit described in this Title V operating permit as being fired on natural gas, shall only use Public Utility Commission (PUC)-quality natural gas, unless the emission unit permit specifies otherwise. [Rule(s) 53, 62]
2. Records required by this permit shall be considered as being maintained "on-site" if records for the previous 12-month period are available at the San Diego NEO San Diego LLC field office and any additional records are maintained at the NEO San Diego LLC Lockport, NY offices and made readily available to the District upon request. [Rule 21]

SECTION III. EMISSION UNIT REQUIREMENTS

A. DISTRICT PERMITTED EMISSION UNITS

The District Permits listed below and attached in Appendix A, including all terms and conditions of such permits, constitute the emission unit portion of this Title V Operating Permit document.

Permit Number	Source Category
APCD2007-PTO-950804	Landfill Gas Collection System and Flare System

B. REGISTERED AND LEASED EMISSION UNITS

The permittee shall comply with the source specific applicable requirements specified in the Rules and Regulations cited below for all registered emission units, unless specifically exempted by the same Rule or Regulations.

Regulation	Rule Citation	Title
SDCAPCD Reg. IV	52	Particulate Matter
SDCAPCD Reg. IV	53	Specific Contaminants
SDCAPCD Reg. IV	54	Dust and Fumes
SDCAPCD Reg. IV	62	Sulfur Content of Fuels
SDCAPCD Reg. IV	67.6	Solvent Cleaning Operations
SDCAPCD Reg. IV	69.4	Stationary Reciprocating Internal Combustion Engines

C. INSIGNIFICANT EMISSION UNITS AND ACTIVITIES

The permittee shall comply with the source specific applicable requirements in the District Rules and Regulations, including those listed below, for any Insignificant Units located at this facility that are listed at District Regulation XIV, Appendix-A, for which a permit is not required.

Regulation	Rule Citation	Title
SDCAPCD Reg. IV	52	Particulate Matter
SDCAPCD Reg. IV	53	Specific Contaminants
SDCAPCD Reg. IV	54	Dust and Fumes
SDCAPCD Reg. IV	62	Sulfur Content of Fuels
SDCAPCD Reg. IV	66	Organic Solvents

SECTION IV. DISTRICT-ONLY PROVISIONS

A. VARIANCE PROCEDURES

The permittee may seek relief from District enforcement action from District-only provisions in the event of a breakdown in accordance with District Rule 98. Notwithstanding the foregoing, the granting by the District of breakdown relief or the issuance by the Hearing Board of a variance does not provide relief from federal enforcement or citizen's suits. [Rule 98]

SECTION V. APPENDICES

APPENDIX A: DISTRICT PERMITS

Permit Number	Source Category
APCD2007-PTO-950804	Landfill Gas Collection System and Flare System

COUNTY OF SAN DIEGO, AIR POLLUTION CONTROL DISTRICT
10124 OLD GROVE RD, SAN DIEGO, CA 92131
(858) 586-2600 FAX (858) 586-2601

PERMIT NO
APCD2007-PTO-950804

PERMIT TO OPERATE

This permit is not valid until required fees have been paid.

The following is hereby granted a Permit To Operate the article, machine, equipment or contrivance described below. This permit is not transferable to a new owner nor is it valid for operation of the equipment at another location except as specified. This permit to operate or copy must be posted on or within 25 feet of the equipment, or readily available on the operating premises.

Neo San Diego LLC
General Manager
5087 Junction Rd
Lockport NY 14094

EQUIPMENT ADDRESS
Neo San Diego LLC
5344 Convoy St
San Diego CA 92111

EQUIPMENT DESCRIPTION

A landfill gas collection and condensate management system consisting of multiple gas collection wells and all associated piping, valves, fittings, sample points, liquid pumps, liquid storage tanks, and landfill gas blower(s). This equipment shall also include a landfill gas combustion system consisting of two enclosed ground flares (approximately 11 ft diameter and 38 ft height), each equipped with an optical flame detector, automatic shutoff valve, stack thermocouples, flame arrestor, and exhaust gas sampling ports. The flare station control and monitoring system shall include, at a minimum, an in-line gas oxygen analyzer, a landfill gas flow meter, an exhaust gas stack temperature recorder, and a supplemental fuel supply.

EVERY PERSON WHO OWNS OR OPERATES THIS EQUIPMENT IS REQUIRED TO COMPLY WITH THE CONDITIONS LISTED BELOW AND ALL APPLICABLE REQUIREMENTS AND DISTRICT RULES, INCLUDING BUT NOT LIMITED TO RULES 10, 20, 40, 50, 51.

Fee Schedules: 2 [48C] Waste Disposal Site/Landfill
BEC: 10998

FEDERALLY-ENFORCEABLE AND DISTRICT-ENFORCEABLE CONDITIONS

1. The Permittee is subject to and shall comply with the applicable requirements of District Rules 53 and 59, and 40 CFR 60 Subpart WWW and 40 CFR 63 Subpart AAAA. These requirements include, but may not be limited to, the related conditions of this permit.
2. The collected landfill gas temperature shall be maintained at less than 55° C at each well and the oxygen level shall be less than or equal to 5 percent. The permittee may establish a higher operating temperature, nitrogen, or oxygen value at a particular well. A higher operating value demonstration

shall show supporting data that the elevated parameter does not cause fires or significantly inhibit anaerobic decomposition by killing methanogens. [40 CFR 60.753(c)]

3. Temperature gauge maintenance and calibration records shall be maintained for at least five years and made available to the District upon request. [40 CFR 60.758]
4. The Permittee shall maintain a negative pressure within each gas extraction well except under the following conditions:
 - a. A fire or increased well temperature. The owner or operator shall record instances when positive pressure occurs in efforts to avoid a fire. These records shall be submitted with the annual reports as provided in §60.757(f).
 - b. Use of a Geomembrane or synthetic cover
 - c. Decommissioned well

The permittee shall record instances when positive pressure occurs and actions taken. An operating pressure gauge with an accuracy of 1 percent of the pressure measured shall be provided to the District upon request for verifying the pressure. The pressure gauge shall be maintained and calibrated in accordance with the manufacturer's specifications.

[40 CFR §§ 60.753(b) and 60.756(a); 17 CCR 95464(c)]

5. The Permittee shall on a monthly basis monitor or conduct testing to verify compliance as follows: record pressure, temperature and nitrogen or oxygen content at each well head. The nitrogen level shall be determined using EPA Method 3C or the oxygen level shall be determined using EPA Method 3A except that:
 - a. The span shall be set so the regulatory limit is between 20 and 50 percent of the span.
 - b. A data recorder is not required.
 - c. Only two calibration gases are required, a zero and a span, and ambient air may be used as the span.
 - d. A calibration error check is not required.
 - e. The allowable sample bias, zero drift and calibration drift are +/- 10 percent.

[40 CFR 60.755(a)(5)]

6. The Permittee shall route all the collected landfill gas to the landfill gas destruction system. [40 CFR 60.752(b)(2)(iii); 17 CCR 95464(b)(1)(A)]
7. The landfill gas destruction system shall be operated to reduce non-methane organic compounds (NMOC) by 98 weight percent or reduce the NMOC outlet concentration to less than 20 ppmv dry basis as hexane at 3 percent oxygen. [40 CFR 60.752(b)(2)(iii)(B)]
8. The Permittee shall monitor the flare exhaust gas temperature. The gas temperature monitoring device shall be equipped with a continuous recorder which has an accuracy of +/- 1 percent of the temperature being measured. [40 CFR 60.756(b)(1); 17 CCR 95464(b)(2)(A)]
9. The Permittee shall monitor and record gas flow from the collection system to the flare at least once every 15 minutes. [40 CFR 60.756(b)(2)(i)]
10. The system shall be continuously monitored for the presence of a flare flame. [40 CFR 60.758(b)(4)]

11. In the event the collection or control system is inoperable, the gas mover system shall be shut down and all valves in the collection and control system contributing to venting of the gas to the atmosphere shall be closed within 1 hour. [40 CFR 60.753(e)]
12. The flow rate of landfill gas shall not exceed 3000 scfm per flare. A meter shall be installed at the flare station which measures and displays the landfill gas flow rate to each flare. Permittee shall calibrate this meter at least annually. [NSR]
13. Except for a flare ignition and startup not to exceed 15 minutes, Permittee shall ensure complete combustion of landfill gases during operation by maintaining the stack gas exit temperature at no less than 1500° F or as otherwise specified by the flare manufacturer. Supplemental fuel (natural gas or propane) shall be added as necessary to maintain the required stack gas exit temperature. [NSR]
14. The Permittee shall record all flare monitoring data and shall keep a record of all periods when the flare is non-operational. [40 CFR 60.758(b)]
15. The Permittee shall record all values which exceed the operation standards for pressure, temperature and nitrogen or oxygen concentration specified in this permit and in 40 CFR Part 60.753 and shall include the operating value from the next subsequent monitoring period and the location of each exceedance. [40 CFR 60.758(e)]
16. The Permittee shall maintain, readily accessible records for the life of the control equipment, the control device vendor specifications and the following data as measured during the initial performance test or compliance determination:
 - a. the maximum expected gas generation flow rate as calculated in 40 CFR Part 60.755(a)(1).
 - b. the density of wells, horizontal collectors, surface collectors or other gas extraction devices determined using the procedures specified in 40 CFR Part 60.759 (a)(1). [40 CFR 60.758(b)]
17. The Permittee shall submit semi-annual reports no later than March 1 and September 1 with the following required information:
 - a. The value and length of time for exceedances of applicable parameters monitored as required in 40 CFR Parts 60.753 and 60.756;
 - b. A description and the duration of all periods when all combustion devices were not operating for any period exceeding 1 hour and the length of time all combustion devices were not operating; and
 - c. All periods in excess of five days during which the landfill gas collection system was not operating.[40 CFR 60 Subpart WWW]
18. All 3 hour periods of operation during which the average flare combustion temperature was more than 28° C (50° F) below the average combustion temperature during the most recent performance test at which compliance with Sec. 60.752 (b)(2)(iii) was determined shall be recorded and reported under § 60.757(f). [40 CFR 60.757(f)]
19. The above equipment shall be properly maintained and operational at all times except as necessary for maintenance and repair. Calibration and maintenance records required by this permit shall be retained at the field office of NEO San Diego LLC and made available to the District upon request. [NSR]

20. All collected landfill gas not delivered to the permitted Miramar Cogeneration facility (District ID APCD1996-SITE-09778) and the North City Cogeneration facility (District ID APCD1996-SITE-09688) shall be incinerated in the flare. [40 CFR 60.753(e) and (f)]
21. The Permittee shall keep the following records:
 - a. The occurrence and duration of each startup, shutdown, or malfunction of operation.
 - b. The occurrence and duration of each malfunction of the required Air Pollution control and monitoring equipment.
 - c. All required maintenance performed on the Air Pollution Control and monitoring equipment.
 - d. Actions taken during periods of startup, shutdown, and malfunction when such actions are different from the procedures specified in the startup, shutdown, and malfunction (SSM) plan.
 - e. All information necessary to demonstrate conformance with the affected source's SSM plan when actions taken during periods of SSM are consistent with the procedures specified in the SSM plan.

The Permittee shall report action(s) recorded above to the District during the applicable semi-annual reporting period.

[40 CFR 63 Subpart AAAA; 40 CFR 63.6(e)]
22. The Permittee shall report actions taken during a SSM event that are not consistent with the SSM plan and the source exceeds any applicable emissions limitation to the District within 2 working days after commencing actions inconsistent with the SSM plan and shall report such actions in writing to the District within 7 working days after the end of the event. [40 CFR 63 Subpart AAAA; 40 CFR 63.6(e)]
23. The Permittee shall maintain a copy of the current startup, shutdown, and malfunction (SSM) plan for at least five years, and make the SSM plan available to the District upon request. Each previous version of the SSM plan shall be maintained for at least 5 years from the date of the SSM plan revision. [40 CFR 63 Subpart AAAA; 40 CFR 63.6(e)]
24. If the SSM plan fails to address or inadequately addresses an event that meets the definition of a malfunction but was not included in the SSM plan, the Permittee shall revise the SSM plan within 45 days after the event to include procedures for operating and maintaining the source during similar malfunction events and a program of corrective action for similar malfunctions. The revised SSM plan shall not take effect until after the owner or operator has provided a written notice describing the SSM plan revision to the District. [40 CFR 63 Subpart AAAA; 40 CFR 63.6(e)]
25. Any SSM plan revision which alters the scope of the activities at the source which are deemed to be a startup, shutdown, or malfunction, or otherwise modifies the applicability of any emission limit, work practice requirement, or other requirement in a standard established under this part, the revised plan shall not take effect until after notice has been provided to the District. [40 CFR 63 Subpart AAAA; 40 CFR 63.6(e)]
26. Each SSM plan revision shall be reported in the semi-annual report covering the reporting period in which the SSM plan was revised. [40 CFR 63 Subpart AAAA; 40 CFR 63.6(e)]
27. Should the District, or the San Diego County Health Department or any health agency of the state of California determine that an imminent threat exists onsite, endangering human life and requiring immediate action, the owner/operator shall take whatever actions are deemed necessary by the

District and/or the health agency to protect human health. [California Health and Safety Code Section 25358.3]

28. Emissions of sulfur compounds from this emission unit, calculated as sulfur dioxide, shall not exceed 0.05% by volume on a dry basis. [Rule 53]
29. Emissions of combustion particulates shall not exceed 0.10 grains per dry standard cubic foot standardized to 12 percent carbon dioxide by volume. [Rule 53]
30. If requested by the District or EPA, emissions of sulfur compounds and/or combustion particulates shall be measured in accordance with EPA reference methods or equivalent methods as approved by the District. [Rule 53; Rule 21]
31. Emissions of NO_x from any fuel combustion equipment with an input rating of 50 million Btu/hr or greater shall not exceed 125 ppmv calculated as nitrogen dioxide @ 3% oxygen on a dry basis. [Rule 68]
32. The applicable test methods listed in Rule 68 Section (f) and SDCAPCD Test Method 100 shall be used to determine compliance with the NO_x emission limits listed above. [Rule 68]
33. The Permittee shall acquire the required permit(s) from the District prior to any expansion of the landfill or changes in the landfill gas collection system . [Rule 10]
34. Access, facilities, utilities and any necessary safety equipment for source testing and inspection shall be provided upon request of the Air Pollution Control District. [Rule 19]

DISTRICT-ONLY-ENFORCEABLE CONDITIONS

35. The Permittee shall operate, adjust, and maintain the gas collection system to prevent excessive quantities of air from being drawn into the landfill. An oxygen analyzer, designed to be accurate to +/- 0.5% by volume, shall be installed in the collection piping at the flare station, maintained in good working condition, and calibrated at least biennially. The concentration of oxygen in Landfill gas at the flare station shall not exceed 3.5% by volume. Analyzer calibration records shall be maintained for at least five years and made available to the District upon request. [Rule 59(d)(6)]
36. A shut-off valve shall be in place and maintained at each well head. [Rule 59]
37. An automatic shutoff device shall stop the flow of landfill gas to the flare whenever conditions of flame-out, excessive exhaust gas temperature (>1800° F) or excessive landfill gas oxygen content (>3.5% by volume) occur. [Rule 59]
38. There shall be no leaks of landfill gas from the collection system and flare equipment in excess of 1375 ppmv (measured as methane) at a distance of ½ inch from the transfer path, other than non-repeatable, momentary readings. This requirement does not apply during active maintenance, repair, or sampling activities. [Rule 59(d)(3)]
39. There shall be no release of leachate or condensate from any part of the landfill gas collection system or flare station, which results in the discharge of non-methane organic compounds to the atmosphere. [Rule 59]
40. This Air Pollution Control District Permit does not relieve the holder from obtaining permits or authorizations required by other governmental agencies.

41. The permittee shall, upon determination of applicability and written notification by the District, comply with all applicable requirements of the Air Toxics "Hot Spots" Information and Assessment Act (California Health and Safety Code Section 44300 et seq.)
42. The permittee is subject to Title 17 California Code of Regulations (CCR) SUBARTICLE 6. METHANE EMISSIONS FROM MUNICIPAL SOLID WASTE LANDFILLS (§§ 95460 – 95476 and Appendix I), which includes, but may not be limited to, the requirements cited in this permit. [17 CCR § 95461]
43. The permittee shall operate the gas collection and control system in accordance with 17 CCR section 95464(b), which includes, but is not limited to, the following:
 - a. Route the collected gas to a gas control device or devices except as provided in 17 CCR sections 95464(d) - well raising, and 95464(e) - Repairs and Temporary Shutdown of Gas Collection System Components;
 - b. So that there is no landfill gas leak that exceeds 500 ppmv, measured as methane, at any component under positive pressure. Measurement for this determination shall be made at a distance of one half of an inch or less for a component source that exceeds 500 parts per million by volume (ppmv), excluding non-repeatable, momentary readings; measurement of leaks from any vault must be taken within 3 inches above the surface of the vault exposed to the atmosphere. [17 CCR § 95464(b)(1)(B) and the definition of component leak at § 95475];
 - c. So that all the landfill gas is drawn toward the gas control device or devices;
 - d. So that each wellhead remains under vacuum (negative pressure), except under the following conditions:
 1. Use of a geomembrane or synthetic cover, provided permittee establishes acceptable pressure limits for the wellheads and includes them in the Design Plan;
 2. A decommissioned well;
 3. Well raising activities in which new fill is being added or compacted in the immediate vicinity around the well, or a well extension that, once installed, is sealed or capped until the raised well is reconnected to a vacuum source.

[17 CCR §§ 95464(b)(1), 95464(c), 95464(d) and 95475]
44. Except as provided in sections 95464(d), 95464(e), and 95466, no location on the landfill surface may exceed either of the following concentrations of methane:
 - a. 500 ppmv, other than non-repeatable, momentary readings, as determined by instantaneous surface emissions monitoring, measured at a distance of 3 inches above surface as required by § 95471(c)(1)(A);
 - b. An average of 25 ppmv as determined by integrated surface emissions monitoring.

[17 CCR § 95465]
45. The requirements of section 95465 do not apply to the working face of the landfill or to areas of the landfill surface where the landfill cover material has been removed and refuse has been exposed for the purpose of installing, expanding, replacing, or repairing components of the landfill gas, leachate,

or gas condensate collection and removal system, or for law enforcement activities requiring excavation. [17 CCR § 95466]

46. If the permittee operates a flare for the control of landfill gas, the flare must meet the following requirements:

- a. Achieves a methane destruction efficiency of at least 99 percent by weight;
- b. Is equipped with automatic dampers, an automatic shutdown device, a flame arrester, and continuous recording temperature sensors;
- c. During startup or restart there must be sufficient flow of propane or commercial natural gas to the burners to prevent unburned collected methane from being emitted to the atmosphere;
- d. The gas control device must be operated within the parameter ranges established during the initial or most recent source test.

[17 CCR § 95464(b)(2)(A)]

47. The permittee must conduct an annual source test for flare control efficiency using the test methods identified in 17 CCR 95471(f). Each succeeding complete annual source test must be conducted no later than 45 days after the anniversary date of the initial source test.

If a gas control device remains in compliance after three consecutive source tests the permittee may conduct the source test every three years. If a subsequent source test shows the gas collection and control system is out of compliance the source testing frequency will return to annual. [17 CCR § 95464(b)(4)]

48. The requirements of 17 CCR sections 95464(b)(1)(A), 95464(b)(1)(B), and 95464(c) do not apply to individual landfill gas collection system components that must be temporarily shut down in order to repair the components, due to catastrophic events such as earthquakes, to connect new landfill gas collection system components to the existing system, to extinguish landfill fires, or to perform construction activities pursuant to section 95466, provided the following requirements are met:

- a. Any new gas collection system components required to maintain compliance with 17 CCR 95464 must be included in the most recent Design Plan pursuant to section 95464(a)(4);
- b. Methane emissions must be minimized during shutdown pursuant to section 95464(a)(1)(D).

[17 CCR § 95464(e)(1-2)]

49. The permittee must monitor each individual wellhead monthly to determine the gauge pressure. If there is any positive pressure reading other than as provided in 17 CCR sections 95464(d) and 95464(e), the permittee must take the following actions:

- a. Initiate corrective action within five calendar days of the positive pressure measurement;

- b. If the problem cannot be corrected within 15 days of the date the positive pressure was first measured, the owner or operator must initiate further action, including, but not limited to, any necessary expansion of the gas collection system, to mitigate any positive pressure readings;
- c. Corrective actions, including any expansion of the gas collection and control system, must be completed and any new wells must be operating within 120 days of the date the positive pressure was first measured, or it is a violation.

[17 CCR § 95469(c)]

50. Components containing landfill gas that are under positive pressure must be monitored quarterly for leaks. Any component leak must be tagged and repaired within 10 calendar days, or it is a violation.

[17 CCR § 95469(b)(3)]

51. Component leak testing at MSW landfills having landfill gas-to-energy facilities may be conducted prior to scheduled maintenance or planned outage periods. [17 CCR § 95469(b)(3)(A)]

52. The permittee must conduct quarterly surface monitoring in accordance with 17 CCR section 95469 using the equipment and procedures specified in section 95471. Instantaneous surface monitoring shall be conducted using either an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications given at 17 CCR § 95471(a) and using the applicable procedures given at 17 CCR § 95471(c) including, but not limited to, the monitoring grid layout.

[17 CCR § 95469(a)]

53. Instantaneous Surface Monitoring under 17 CCR SUBARTICLE 6: Pursuant to section 95465(a)(1), any landfill surface reading exceeding 500 ppmv, other than non-repeatable, momentary readings, as determined by instantaneous surface emissions monitoring, must be recorded as an exceedance and the following actions taken:

- a. The permittee must record the date, location, and value of each exceedance, along with re-test dates and results. The location of each exceedance must be clearly marked and identified on a topographic map of the MSW landfill, drawn to scale with the location of both the grids and the gas collection system clearly identified.
- b. Corrective action must be taken by the owner or operator such as, but not limited to, cover maintenance or repair, or well vacuum adjustments and the location must be re-monitored within ten calendar days of a measured exceedance.
 - 1. If the re-monitoring of the location shows a second exceedance, additional corrective action must be taken and the location must be re-monitored again no later than 10 calendar days after the second exceedance.
 - 2. If the re-monitoring shows a third exceedance, the owner or owner or operator must install a new or replacement well, unless an alternative solution is identified and approved by the District, as determined to achieve compliance no later than 120 calendar days after detecting the third exceedance, or it is a violation of this subarticle.
- c. Any closed or inactive MSW landfill, or any closed or inactive areas on an active MSW landfill that has no monitored exceedances of the 500 ppmv methane limit specified in section

95465(a)(1) after four consecutive quarterly monitoring periods may monitor annually. Any exceedances of this limit detected during the annual monitoring that cannot be remediated within 10 calendar days will result in a return to quarterly monitoring of the landfill.

- d. Any exceedances of the 500 ppmv methane limit specified in section 95465(a)(1) detected during any compliance inspections will result in a return to quarterly monitoring of the landfill.
- e. Any instantaneous methane measurement of 200 ppmv or greater must be recorded as a reportable reading pursuant to 17 CCR 95971(a)(1)(D).

[17 CCR §§ 95969(a)(2) and 95971]

54. Integrated Surface Monitoring under 17 CCR SUBARTICLE 6: Any reading exceeding an average of 25 ppmv as specified in 17 CCR section 95465(a)(2) must be recorded as an exceedance and the following actions must be taken:

- a. The permittee must record the average surface concentration measured as methane for each grid along with re-test dates and results. The location of the grids and the gas collection system must be clearly marked and identified on a topographic map of the MSW landfill drawn to scale.
- b. Within 10 calendar days of a measured exceedance, corrective action must be taken by the owner or operator such as, but not limited to, cover maintenance or repair, or well vacuum adjustments and the grid must be re-monitored.
 - 1. If the re-monitoring of the grid shows a second exceedance, additional corrective action must be taken and the location must be re-monitored again no later than 10 calendar days after the second exceedance.
 - 2. If the re-monitoring in section 95469(a)(2)(B)1. shows a third exceedance, the owner or operator must install a new or replacement well as determined to achieve compliance no later than 120 calendar days after detecting the third exceedance, or it is a violation of this subarticle.
- c. Any closed or inactive MSW landfill, or any closed or inactive areas on an active MSW landfill that has no monitored exceedances of the limit specified in section 95465(a)(2) after 4 consecutive quarterly monitoring periods may monitor annually. Any exceedances of the limits specified in section 95465(a)(2) detected during the annual monitoring that cannot be remediated within 10 calendar days will result in a return to quarterly monitoring of the landfill.
- d. Any exceedances of the limits specified in section 95465(a)(2) detected during any compliance inspections will result in a return to quarterly monitoring of the landfill.

[17 CCR § 95969(a)(2)]

55. An owner or operator of a closed or inactive MSW landfill, or any closed or inactive area on an active MSW landfill, that can demonstrate that in the three years before the effective date of this subarticle that there were no measured exceedances of the limits specified in section 95465 by

annual or quarterly monitoring may monitor annually. Any exceedances of the surface methane emission limits specified in section 95465 detected during the annual monitoring that cannot be remediated within 10 calendar days will result in a return to quarterly monitoring. [17 CCR § 95469(a)(3)]

56. Component Monitoring under 17 CCR SUBARTICLE 6: Components containing landfill gas and under positive pressure must be monitored quarterly for leaks. Any component leak must be tagged and repaired within 10 calendar days, or it is a violation. Component leak testing at MSW landfills having landfill gas-to-energy facilities may be conducted prior to scheduled maintenance or planned outage periods. [17 CCR § 95969(b)(3)]
57. *Recordkeeping – five year retention*, 17 CCR SUBARTICLE 6: In addition to any other records required by this permit, the permittee must maintain the following records for at least five (5) years:
- a. All gas collection system downtime exceeding five calendar days, including individual well shutdown and disconnection times, and the reason for the downtime.
 - b. All gas control system downtime in excess of one hour, the reason for the downtime, and the length of time the gas control system was shutdown.
 - c. Expected gas generation flow rate calculated pursuant to section 95471(e) – 2006 Intergovernmental Panel on Climate Change (IPCC) Guidelines for National Greenhouse Gas Inventories, Chapter 3, using a recovery rate of 75%.
 - d. Records of all instantaneous surface readings of 200 ppmv or greater; all exceedances of the limits in sections 95464(b)(1)(B) or 95465, including the location of the leak (or affected grid), leak concentration in ppmv, date and time of measurement, the action taken to repair the leak, date of repair, any required re-monitoring and the re-monitored concentration in ppmv, and wind speed during surface sampling; and the installation date and location of each well installed as part of a gas collection system expansion.
 - e. Records of any positive wellhead gauge pressure measurements, the date of the measurements, the well identification number, and the corrective action taken.
 - f. Annual solid waste acceptance rate and the current amount of waste-in-place.
 - g. Records of the nature, location, amount, and date of deposition of non-degradable waste for any landfill areas excluded from the collection system.
 - h. Results of any source tests conducted pursuant to section 95464(b)(4).
 - i. Records describing the mitigation measures taken to prevent the release of methane or other emissions into the atmosphere:
 1. When solid waste was brought to the surface during the installation or preparation of wells, piping, or other equipment;
 2. During repairs or the temporary shutdown of gas collection system components;

3. When solid waste was excavated and moved.
- j. Records of any construction activities pursuant to section 95466. The records must contain the following information:
 1. A description of the actions being taken, the areas of the MSW landfill that will be affected by these actions, the reason the actions are required, and any landfill gas collection system components that will be affected by these actions.
 2. Construction start and finish dates, projected equipment installation dates, and projected shut down times for individual gas collection system components.
 3. A description of the mitigation measures taken to minimize methane emissions and other potential air quality impacts.
- k. Records of the equipment operating parameters specified to be monitored under sections 95469(b)(1) and 95469(b)(2) as well as records for periods of operation during which the parameter boundaries established during the most recent source test are exceeded. The records must include the following information:
 1. For enclosed flares, all 3-hour periods of operation during which the average temperature difference was more than 28 degrees Celsius (or 50 degrees Fahrenheit) below the average combustion temperature during the most recent source test at which compliance with sections 95464(b)(2) and 95464(b)(3)(A) was determined.
 2. For boilers or process heaters, whenever there is a change in the location at which the vent stream is introduced into the flame zone pursuant to section 95464(b)(3)(A)2.
 3. For any owner or operator who uses a boiler or process heater with a design heat input capacity of 44 megawatts (150 MMBtu/hr) or greater to comply with section 95464(b)(3), all periods of operation of the boiler or process heater (e.g., steam use, fuel use, or monitoring data collected pursuant to other federal, State, local, or tribal regulatory requirements).

[17 CCR § 95470(a)(1)]

58. *Recordkeeping – retention for life of control device*, 17 CCR SUBARTICLE 6: Permittee must maintain the following records for the life of each gas control device:

- a. The control device vendor specifications.
- b. The expected gas generation flow rate as calculated pursuant to section 95471(e).
- c. The percent reduction of methane achieved by the control device determined pursuant to section 95471(f).
- d. For a boiler or process heater, the description of the location at which the collected gas vent stream is introduced into the boiler or process heater over the same time period of the performance test.

- e. For an open flare: the flare type (i.e., steam-assisted, air-assisted, or non-assisted); all visible emission readings, heat content determination, flow rate or bypass flow rate measurements, and exit velocity determinations made during the performance test as specified in 40 CFR § 60.18 (as last amended 73 Fed.Reg. 78209 (December 22, 2008), which is incorporated by reference herein; and records of the flare pilot flame or flare flame monitoring and records of all periods of operations during which the pilot flame or the flare flame is absent.

[17 CCR § 95470(a)(2)]

59. *Record Storage*: The permittee must maintain copies of the records and reports required by this subarticle and provide them to the District within five business days upon request. Records and reports must be kept at a location within the State of California. [17 CCR § 95470(a)(3)]
60. *Annual Report*: Except as given in 17 CCR section 95463, permittee must prepare an annual report for the period of January 1 through December 31 of each year. Each annual report must be submitted to the District by March 15 of the following year and must contain the following information:
- a. MSW landfill name, owner and operator, address, and solid waste information system (SWIS) identification number.
 - b. Total volume of landfill gas collected (reported in standard cubic feet).
 - c. Average composition of the landfill gas collected over the reporting period (reported in percent methane and percent carbon dioxide by volume).
 - d. Gas control device type, year of installation, rating, fuel type, and total amount of landfill gas combusted in each control device.
 - e. The date that the gas collection and control system was installed and in full operation.
 - f. The percent methane destruction efficiency of each gas control device(s).
 - g. Type and amount of supplemental fuels burned with the landfill gas in each device.
 - h. Total volume of landfill gas shipped off-site, the composition of the landfill gas collected (reported in percent methane and percent carbon dioxide by volume), and the recipient of the gas.
 - i. Most recent topographic map of the site showing the areas with final cover and a geomembrane and the areas with final cover without a geomembrane with corresponding percentages over the landfill surface.
 - j. The information records cited herein and required by sections 95470(a)(1)(A), 95470(a)(1)(B), 95470(a)(1)(C), 95470(a)(1)(D), 95470(a)(1)(E), and 95470(a)(1)(F), 95470(a)(1)(H), and 95470(a)(1)(K).

[17 CCR § 95470(b)(3)]

61. *Waste-in-Place Report*: If the MSW landfill contains less than 450,000 tons of waste-in-place, or the landfill contains 450,000 tons or more of waste-in-place and landfill gas recovery reaches or exceeds

3.0 MMBtu/hr, as given by section 95463(a) or section 95643(b)(2)(B)3., permittee must report the following information to the District:

- a. MSW landfill name, owner and operator, address, and solid waste information system (SWIS) identification number.
- b. The landfill's status (active, closed, or inactive) and the estimated waste-in-place, in tons.
- c. Most recent topographic map of the site showing the areas with final cover and a geomembrane and the areas with final cover without a geomembrane with corresponding percentages over the landfill surface. [17 CCR § 95470(b)(4)]

62. *Landfill Gas Heat Input Capacity Report*: Permittee must calculate the landfill gas heat input capacity as required by section 95463(b) (i.e., gas heat input capacity report requirement for landfills greater than or equal to 450,000 tons of waste-in-place) using the procedures specified in section 95471(b) (i.e., procedure as specified in Appendix I, as applicable) and report the results to the District within 90 days of the effective date of this subarticle or upon reaching 450,000 tons of waste-in-place. The calculation, along with relevant parameters, must be provided as part of the report. [17 CCR § 95470(b)(5)]

63. Any report, or information submitted pursuant to 17 CCR subarticle 6 must contain certification by a responsible official of truth, accuracy, and completeness. This certification, and any other certification required under this subarticle, must state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. [17 CCR § 95470(b)(6)]

64. Each part of 17 CCR Subarticle 6 is deemed severable, and in the event that any part of this subarticle is held to be invalid, the remainder of this subarticle continues in full force and effect. [17 CCR § 95476]

APPENDIX B. RULE REFERENCE TABLE (LAST UPDATED 06/14/11)

Rule Citation¹	RULE TITLE	A/R²	District Adoption Date³	SIP FR Approval Date
	REGULATION I - GENERAL PROVISIONS			
1	Title	F	04/30/80	09/28/81
2	Definitions	F	06/30/99	02/03/00 ⁴
4	Review of Rules	F	01/01/70 [†]	09/22/72
5	Authority to Arrest	F	03/24/76 [†]	05/11/77
	REGULATION II - PERMITS			
10	Permits Required	F	04/27/00	03/11/98
10.1 ^{††}	NSPS & NESHAPS Requirements	D	11/8/76	N/A
11	Exemptions from Rule 10 Permit Requirements	D/F	05/09/12	Pending
12	Registration of Specified Equipment	D	11/15/00	N/A
12.1	Portable Equipment Registration	D	05/21/97	N/A
14	Applications	F	04/30/80	09/28/81
15	Permit Process - Public Notifications	D/F	09/18/90	Pending
17	Cancellation of Applications	F	11/25/81	03/11/98
18	Action on Applications	F	01/17/72	09/22/72
18	Action on Applications	D/F	09/18/90	Pending
19	Provision of Sampling and Testing Facilities	F	04/06/93	03/11/98
19.1 ^{††}	NSPS & NESHAPS Provision of Sampling and Testing Facilities Requirements	D	11/08/76	N/A
19.2	Continuous Emission Monitoring Requirements	F	01/12/79	09/28/81
19.3	Emission Information	F	5/15/96	03/09/00
20	Standards for Granting Permits	D/F	04/25/89	Pending
20.1	Definitions, Emission Calculations, Emission Offsets and Banking, Exemptions, and Other Requirements	F	12/17/98	04/14/81
20.1	NSR - General Provisions	D/F	12/17/98	Pending
20.2	Standards for Authority to Construct - Best Available Air Pollution Control Technology	F	12/17/98	04/14/81
20.2	NSR - Non-major Stationary Sources	D/F	12/17/98	Pending
20.3	Standards for Authority to Construct - Air Quality Analysis	F	12/17/98	04/14/81
20.3	NSR - Major Stationary Source and PSD Stationary Source	D/F	12/17/98	Pending
20.4	Standards for Authority to Construct - Major Stationary Sources	F	12/17/98	04/14/81
20.4	NSR - Portable Emission Units	D/F	12/17/98	Pending
20.5	Power Plants	F	07/05/79	04/14/81
20.6	Standards for Permit to Operate - Air Quality Analysis	F	07/05/79	04/14/81
20.6	Standards for Permit to Operate Air Quality Analysis	D/F	12/14/87	Pending
20.8	Special Offset Requirement Relating to Banking	D	2/16/83	N/A
21	Permit Conditions	F	11/29/94	03/11/98
22	Denial of Applications	F	01/01/69 [†]	09/22/72

23	Further Information	F	01/01/69 [†]	09/22/72
24	Temporary Permit to Operate	F	03/20/96	10/24/08
25	Appeals	F	01/01/69 [†]	09/22/72
25	Appeals	D/F	06/21/00	Pending
26.0	Banking of Emission Reduction Credits (ERCs) - General Requirements	D/F	10/22/97	Pending
26.1	Standards for Granting Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.2	Use of Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.3	Reclassification of Class B Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.4	Permanency of Banked Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.5	Transfer of Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.6	District Banking of Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.7	Shutdown and Related Emission Unit	D/F	10/22/97	Pending
26.8	Banking of Limited Emission Reductions	D/F	10/22/97	Pending
26.9	Emission Reduction Credit Certificates and The Emission Reduction Credit Register	D/F	10/22/97	Pending
26.10	Banking For BRAC Military Base Closure or Realignment Actions	D/F	10/22/97	Pending
27	Banking of Mobile Source Emission Reduction Credits	D/F	11/29/94	Pending
27.1	Federal Requirements for San Diego County APCD Alternative Mobile Source Emission Reduction Program Approved On 9/8/2000	F	08/06/08	06/03/09
	REGULATIONS III - FEES			
40	Permit Fees	D	01/01/12	N/A
42	Hearing Board Fees	D	07/01/00	N/A
44	Technical Reports, Charges for	D	12/7/83	N/A
	REGULATIONS IV - PROHIBITIONS			
50	Visible Emissions	F	08/13/97	12/7/98
50.1 ^{††}	NSPS & NESHAPS Visible Emissions Requirements	D	11/08/76	N/A
51	Nuisance	F	01/01/69 [†]	09/22/72
52	Particular Matter	F	01/22/97	12/9/98
52.1 ^{††}	NSPS & NESHAPS Particular Matter Requirements	D	11/08/76	N/A
53	Specific Contaminants	F	01/22/97	12/9/98
53.1	Scavenger Plants	F	01/01/69 [†]	09/22/72
53.2 ^{††}	NSPS & NESHAPS Specific Contaminants Requirements	D	11/08/76	N/A
54	Dusts and Fumes	F	01/22/97	12/9/98
54.1	NSPS & NESHAP Dust and Fumes Requirement	D	11/08/76	N/A
58	Incinerator Burning	F	01/17/73 [†]	05/11/77
59	Control of Waste Disposal - Site Emissions	D	11/03/87	Withdrawn
59.1	Municipal Solid Waste Landfills	D	06/17/98	N/A
60	Circumvention	F	05/17/94	03/09/00
60.2	Limiting Potential to Emit - Synthetic Minor Sources	D	04/04/12	N/A
61.0	Definitions Pertaining to the Storage & Handling of Organic Compounds	F	10/16/90	09/13/93

61.1	Receiving & Storing Volatile Organic Compounds at Bulk Plants & Bulk Terminals	F	01/10/95	08/08/95
61.2	Transfer of Volatile Organic Compounds into Mobile Transport Tanks	F	07/26/00	08/26/03
61.3	Transfer of Volatile Organic Compounds into Stationary Storage Tanks	F	10/16/90	06/30/93
61.3.1	Transfer of Gasoline into Stationary Underground Storage Tanks	D	03/01/06	N/A
61.4	Transfer of Volatile Organic Compounds into Vehicle Fuel Tanks	F	10/16/90	05/13/93
61.4	Transfer of Volatile Organic Compounds into Vehicle Fuel Tanks	D/F	03/26/08	Pending
61.4.1	Transfer of Gasoline from Stationary Underground Storage Tanks into Vehicles Fuel Tanks	D	03/01/06	N/A
61.5	Visible Emission Standards for Vapor Control Systems	F	09/20/78 [†]	04/14/81
61.6	NSPS Requirements for Storage of Volatile Organic Compounds	D	01/13/87	Withdrawn
61.7	Spillage and Leakage of Volatile Organic Compounds	F	01/13/87	03/11/98
61.8	Certification Requirements for Vapor Control Equipment	F	01/13/87	03/11/98
62	Sulfur Content of Fuels	F	10/21/81	07/06/82
62.1 ^{††}	NSPS Requirements for Sulfur Content of Fuels	D	11/08/76	N/A
64	Reduction of Animal Matter	F	08/21/81	07/06/82
66	Organic Solvents	F	07/25/95	08/11/98
66.1	Miscellaneous Surface Coating Operations and Other Processes Emitting VOCs	D/F	2/24/10	Pending
67.0	Architectural Coatings	F	04/09/03	03/27/97
67.0	Architectural Coatings	D/F	12/12/01	Pending
67.1	Alternative Emission Control Plans	F	05/15/96	03/27/97
67.2	Dry Cleaning Equipment Using Petroleum - Based Solvent	F	05/15/96	03/27/97
67.3	Metal Parts and Products Coating Operations	F	05/15/96	03/27/97
67.4	Metal Container, Metal Closure and Metal Coil Coating Operations	F	05/15/96	11/03/97
67.5	Paper, Film and Fabric Coating Operations	F	05/15/96	03/27/97
67.6.1	Cold Solvent Cleaning and Stripping Operations	F	5/23/07	10/13/09
67.6.2	Vapor Degreasing Operations	F	5/23/07	10/13/09
67.7	Cutback and Emulsified Asphalts	F	05/15/96	03/27/97
67.9	Aerospace Coating Operations	F	04/30/97	08/17/98
67.10	Kelp Processing and Bio-Polymer Manufacturing	F	06/25/97	06/22/98
67.11	Wood Parts and Products Coating Operations	D/F	09/25/02	Pending
67.11.1	Large Coating Operations for Wood Products	F	09/25/02	06/05/03
67.12	Polyester Resin Operations	F	05/15/96	03/27/97
67.15	Pharmaceutical and Cosmetic Manufacturing Operations	F	05/15/96	03/27/97
67.16	Graphic Arts Operations	F	05/09/12	03/27/97
67.17	Storage of Materials Containing Volatile Organic Compounds	F	05/15/96	03/27/97
67.18	Marine Coating Operations	F	05/15/96	03/27/97
67.19	Coating and Printing Inks Manufacturing Operations	F	05/15/96	01/19/00
67.20.1	Motor Vehicle and Mobile Equipment Coating Operations	D	06/30/10	N/A

67.21	Adhesive Material Application Operations	D	11/14/08	N/A
67.22	Expandable Polystyrene Foam Products Manufacturing Operations	D	05/15/96	N/A
67.24	Bakery Ovens	F	05/15/96	03/27/97
68	Fuel-Burning Equipment – Oxides of Nitrogen	F	09/20/94	04/09/96
68.1††	NSPS Requirements for Oxides of Nitrogen from Fuel-Burning Equipment	D	11/08/76	N/A
69	Electrical Generating Steam Boilers, Replacement Units & New Units	D	12/12/95	N/A
69.2	Industrial & Commercial Boilers, Process Heaters & Steam Generators	F	09/27/94	02/09/96
69.2.1	Small Boilers, Process Heaters and Steam Generators	D	03/25/10	N/A
69.3	Stationary Gas Turbine Engines	F	09/27/94	06/17/97
69.3	Stationary Gas Turbine Engines – RACT	D/F	12/16/98	Pending
69.3.1	Stationary Gas Turbine Engines – BARCT	D	02/24/10	N/A
69.4	Stationary Internal Combustion Engines	F	09/27/94	01/22/97
69.4	Stationary Internal Combustion Engines – RACT	D/F	07/30/03	2/25/04
69.4.1	Stationary Internal Combustion Engines - BARCT	D	11/15/00	N/A
69.5	Natural Gas-Fired Water Heaters	D	01/01/99	N/A
69.6	Natural Gas-Fired Fan-Type Central Furnaces	D	06/17/98	N/A
70	Orchard Heaters	F	01/17/72	09/22/72
71	Abrasive Blasting	F	03/30/77	08/31/78
	REGULATION V - PROCEDURES BEFORE THE HEARING BOARD			
75	Procedure Before the Hearing Board	D/F	09/17/85	Pending
75.1††	NSPS & NESHAPS Variance Procedures	D	09/17/85	7/30/79
97	Emergency Variance	D/F	07/25/95	Pending
98	Breakdown Conditions: Emergency Variance	D	07/25/95	Withdrawn
	REGULATION VI - BURNING CONTROL			
101	Burning Control	F	09/25/02	04/30/03
	REGULATION VII - VALIDITY AND EFFECTIVE DATE			
140	Validity	F	01/01/69†	09/22/72
141	Effective Date	F	01/01/69†	09/22/72
	REGULATION VIII - SAN DIEGO AIR POLLUTION EMERGENCY PLAN			
126	Applicability	F	05/25/77	08/31/78
127	Episode Criteria Levels	F	09/17/91	03/18/99
128	Episode Declaration	F	09/17/91	03/18/99
129	Episode Termination	F	05/25/77	08/31/78
130	Episode Actions	F	09/17/91	03/18/99
131	Stationary Source Curtailment Plan	F	04/01/81	06/21/82
132	Traffic Abatement Plan	F	04/01/81	06/21/82
132	Traffic Abatement Plan	D/F	12/17/97	Pending

133	Schools	F	05/25/77	08/31/78
134	Source Inspection	F	04/01/81	06/21/82
135	Air Monitoring Stations	F	05/25/77	08/31/78
136	Interdistrict and Interbasin Coordination	F	05/25/77	08/31/78
137	Emergency Action Committee	F	05/25/77	08/31/78
138	Procedures and Plans	F	05/25/77	08/31/78
	APPENDIX A - Persons to be Notified on Episode Declaration	F		
REGULATION IX - PUBLIC RECORDS				
175	General	F	05/22/74†	05/11/77
176	Information Supplied to District	F	05/22/74†	05/11/77
177	Inspection of Public Records	F	03/30/77	08/31/78
177	Inspection of Public Records	D/F	06/20/01	Pending
REGULATION XII - TOXIC AIR CONTAMINANTS				
1200	Toxic Air Contaminants - New Source Review	D	06/12/96	N/A
1202	Hexavalent Chromium - Cooling Towers	D	07/25/95	N/A
1203	Ethylene Oxide Sterilizers and Aerators	D	07/26/00	N/A
1205	Control of Dioxins Emissions from Medical Waste Incinerators	D	01/01/94	N/A
1210	Toxic Air Contaminant Public Health Risks - Public Notification and Risk Reduction	D	06/12/96	N/A

REGULATION XIV - TITLE V OPERATING PERMITS				
1401	General Provisions	F	02/27/04	02/27/04
1410	Permit Required	F	02/27/04	02/27/04
1411	Exemption from Permit to Operate for Insignificant Units	F	03/07/95	11/30/01
1412	Federal Acid Rain Program Requirements	F	01/18/94	11/30/01
1413	Early Reduction of Hazardous Air Pollutants	F	03/07/95	11/30/01
1414	Applications	F	03/07/95	11/30/01
1415	Permit Process-Public Notification	F	02/27/04	02/27/04
1417	Pendency & Cancellation of Applications	F	03/07/95	11/30/01
1418	Action on Applications	F	02/27/04	11/30/01
1419	Provisions of Sampling & Testing Facilities & Emission Information	F	03/07/95	11/30/01
1420	Standards for Granting Permits	F	03/07/95	11/30/01
1421	Permit Conditions	F	02/27/04	02/27/04
1422	Denial or Cancellation Of Applications	F	03/07/95	11/30/01
1423	Further Information	F	01/18/94	11/30/01
1424	Applications Deemed Denied	F	01/18/94	11/30/01
1425	Appeals & Judicial Review	F	02/27/04	02/27/04
	APPENDIX A - Insignificant Units	F	02/27/04	11/30/01
REGULATION XV - FEDERAL CONFORMITY				
1501	Conformity of General Federal Actions	F	06/22/99	04/23/99

The following NSPS and NESHAP have been adopted locally by the District. EPA has granted the District delegation for each of these rules. Therefore, these rules, as adopted by the District are the federally applicable requirements. For all other NSPS and NESHAP, the versions cited in the CFR are the federally applicable requirements.

Subpart & Citation	RULE TITLE	District Adoption Date	Federal Delegation Date
Part 60 REGULATION X - STANDARDS OF PERFORMANCE FOR NEW STATIONARY SOURCES			
A	General Provisions	Unknown 11/03/92	11/08/76
E	Standards of Performance for Incinerators	Unknown	03/30/77
I	Standards of Performance for Asphalt Concrete Plants	Unknown 01/13/87	11/08/76
L	Standards of Performance for Secondary Lead Smelters	Unknown	11/08/76
M	Standards of Performance for Secondary Brass and Bronze Ingot Production Plants	Unknown 09/17/85*	03/30/77
O	Standards of Performance for Sewage Treatment Plants	01/13/87	09/17/87
DD	Standards of Performance for Grain Elevators	Unknown	05/24/82
EE	Standards of Performance for Surface Coating Metal Furniture	03/04/86 11/03/92	03/19/87
QQ	Standards of Performance for the Graphic Arts Industry: Publication Rotogravure Printing	08/24/83	12/22/83
RR	Standards of Performance for Pressure Sensitive Tape and Label Surface Coating Operations	09/17/86 11/03/92	03/19/87
SS	Standards of Performance for the Industrial Surface Coating Large Appliances	02/22/84 11/03/92*	04/24/84
TT	Standards of Performance for Metal Coil Surface Coating	02/22/84 11/03/92*	04/24/84
BBB	Standards of Performance for the Rubber Tire Manufacturing Industry	03/14/89	07/18/89
FFF	Standards of Performance for Flexible Vinyl and Urethane Coating and Printing	09/17/86	03/19/87
JJJ	Standards of Performance for Petroleum Dry Cleaners	12/15/87	07/18/89
Part 61 REGULATION XI- NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (NESHAPS)			
A	General Provisions	01/13/87	05/24/82
C	National Emission Standard for Beryllium	Unknown	11/08/76
D	National Emission Standard for Beryllium Rocket Motor Firing	Unknown	11/08/76
E	National Emission Standard for Mercury	03/27/90	05/17/91
F	National Emission Standard for Vinyl Chloride	08/17/77 06/16/78	11/21/77
M	National Emission Standard for Asbestos	06/04/85 02/01/95	07/18/89

The following ATCM and NESHAP have not been adopted by the District, but are being implemented and enforced by the District as ATCM's.

Subpart & Citation	RULE TITLE	A/R	Most Recent Adoption Date
DISTRICT RULES AND REGULATIONS APPENDIX A - CALIFORNIA AIRBORNE TOXIC CONTROL MEASURES (ATCM)			
17 CCR § 93102	Hexavalent Chromium ATCM for Chrome Plating & Chromic Acid Anodizing Operations	D/F	12/7/06
17 CCR § 93109	ATCM For Emissions of Perchloroethylene From Dry Cleaning Operations	F	01/25/07
17 CCR § 93101.5	ATCM to Reduce Emissions of Hexavalent Chromium and Nickel from Thermal Spraying	D	09/30/05
17 CCR § 93105	ATCM for Construction, Grading, Quarrying, and Surface Mining Operations	D	07/26/01
17 CCR § 93106	Asbestos ATCM for Surface Applications	D	07/20/00
17 CCR § 93107	ATCM For Emissions of Toxic Metals From Non-Ferrous Metal Melting	D	01/14/93
17 CCR § 93111	ATCM for Emissions of Chlorinated Toxic Air Contaminants from Automotive Maintenance & Repair Activities	D	04/27/00
17 CCR § 93112	ATCM for Emissions of Hexavalent Chromium and Cadmium from Motor Vehicle and Motor Equipment Coatings	D	09/20/01
17 CCR § 93113	ATCM to Reduce Emissions of Toxic Air Contaminants from Outdoor Residential Waste Burning	D	02/03/03
17 CCR § 93115	ATCM for Stationary Compression Ignition Engines	D	05/19/11
17 CCR § 93116	ATCM for Portable Diesel-Fueled Engines	D	02/19/11
DISTRICT RULES AND REGULATIONS APPENDIX B - NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (NESHAP) FOR SOURCE CATEGORIES			
Part 63			
A	General Provisions	F	05/16/07
N	Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks	F	04/20/06
O	Ethylene Oxide Sterilization Facilities	F	12/28/07
R	Gasoline Distribution	F	01/24/11
T	Halogenated Solvent Cleaning	F	09/08/00
DD	Off-site Waste & Recovery Operations	F	07/20/99
GG	Aerospace Manufacturing and Rework Facilities	F	12/08/00
II	Shipbuilding and Ship Repair (Surface Coating)	F	12/15/95
JJ	Wood Furniture Manufacturing Operations	F	12/28/98
VVV	Publicly Owned Treatment Works	F	10/21/02
AAAA	Municipal Solid Waste Landfills	F	01/16/03
EEEE	Organic Liquids Distribution (non-gasoline)	F	07/17/08
MMMM	Surface Coating of Miscellaneous Metal Parts and Products	F	04/26/04
PPPP	Plastic Parts (surface coating)	F	04/24/07
SSSS	Surface Coating of Metal Coil	F	03/17/03
VVVV	Boat Manufacturing	F	08/22/01

WWWW	Reinforced Plastic Composites Production	F	8/25/05
YYYY	Stationary Combustion Turbines	F	08/18/04
ZZZZ	Stationary Reciprocating Internal Combustion Engines	F	03/09/11
DDDDD	Industrial, Commercial, and Institutional Boilers and Process Heaters	F	05/18/11
GGGGG	Site Remediation	F	11/29/06
HHHHH	Miscellaneous Coating Manufacturing	F	10/04/06
PPPPP	Engine Test Cells/Stands	F	08/28/03
WWWWW	Hospital Ethylene Oxide Sterilizers Area Sources	F	12/28/07
BBBBBB	Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities	F	01/24/11
CCCCCC	Gasoline Dispensing Facilities	F	01/24/11
HHHHHH	Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources	F	01/09/08
JJJJJ	Area Sources: Industrial, Commercial, and Institutional Boilers	F	3/21/11
QQQQQ	Wood Preserving Area Sources	F	07/16/07
VVVVV	Chemical Manufacturing Area Sources	F	11/29/09
WWWWW	Plating and Polishing Operations Area Sources	F	07/01/08
XXXXXX	Metal Fabrication and Finishing Area Sources	F	7/23/08
AAAAAAA	Asphalt Processing and Asphalt Roofing Manufacturing Area Sources	F	12/02/09
CCCCCCC	Paint and Allied Products Manufacture Area Sources	F	12/03/09

The following NSPS have been adopted by the District by reference. The rules listed below are the CFR versions of these rules which are federally applicable requirements.

Subpart & Citation	RULE TITLE	Latest EPA Promulgation Date	District Adoption Date	Delegation Date
Part 60	DISTRICT RULES AND REGULATIONS APPENDIX C - STANDARDS OF PERFORMANCE FOR NEW STATIONARY SOURCES (NSPS)			
D	Standards of Performance for Fossil-Fuel-Fired Steam Generators for Which Construction is Commenced After August 17, 1971	10/17/00 01/28/09	10/17/01 06/24/09	01/03/08 Pending
Da	Standards of Performance for Electric Utility Steam Generating Units for Which Construction is Commenced After September 18, 1978	06/11/01 01/28/09	10/17/01 06/24/09	01/03/08 Pending
Db	Standards of Performance for Industrial-Commercial - Institutional Steam Generating Units	10/01/01 01/28/09	04/25/01 06/24/09	01/03/08 Pending
Dc	Standards of Performance for Small Industrial-Commercial -Institutional Steam Generating Units	05/08/96 01/28/09	08/13/97 06/24/09	06/24/98 Pending
GG	Standards of Performance for Stationary Gas Turbines	06/27/89 02/24/06	10/17/01 02/25/09	01/03/08 Pending
K	Standards of Performance for Storage Vessels for Petroleum Liquids Construct After June 11, 1973 and Prior to May 19, 1978	10/17/00	06/20/07	01/03/08
Ka	Standards of Performance for Storage Vessels for Petroleum Liquids Construction after May 18, 1978	12/14/00	06/20/07	01/03/08
Kb	Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced after July 23, 1984	10/15/03	06/20/07	01/03/08
AAA	Standards of Performance for New Residential Wood Heaters	06/12/99 10/17/00	04/12/00 N/A	01/03/08 N/A
OOO	Standards of Performance for Nonmetallic Mineral Processing Plants	06/09/97 10/17/00	04/28/99 N/A	05/28/02 N/A
UUU	Standards of Performance for Calciners and Dryers in Mineral Industries	07/29/93 10/17/00	11/17/99 N/A	05/28/02 N/A
VVV	Standards for Polymeric Coating of Supporting Substrates Facilities	09/11/89	05/23/07	01/03/08
WWW	Standards of Performance for Municipal Solid Waste Landfills	04/10/00	08/13/97	06/24/98
AAAA	Standards of Performance for Small Municipal Waste Combustion Units	12/06/00	06/20/07	01/03/08
CCCC	Standards of Performance for Commercial and Industrial Solid Waste Incineration Units	12/01/00	06/20/07	01/03/08
EEEE	Standards of Performance for Other Solid Waste Incineration Units	12/16/05	06/20/07	01/03/08
KKKK	Standards of Performance for Stationary Combustion Turbines	07/06/06	02/25/09	06/01/09

The following NSPS have not been adopted by the District and are not delegated to the District. However, the District has the authority to enforce the NSPS through the Title V program. The rules listed below are the CFR versions of these rules, which are federally applicable requirements.

Subpart & Citation	RULE TITLE	Latest EPA Promulgation Date	District Adoption Date	Delegation Date
Part 60				
III	Standards of Performance for Stationary Compression Ignition Internal Combustion Engines	07/11/06	N/A	N/A
JJJ	Standards of Performance for Stationary Spark Ignition Internal Combustion Engines	01/18/08	N/A	N/A

APPENDIX C: ABBREVIATIONS USED IN THIS PERMIT

APCO	Air Pollution Control Officer
ASTM	American Society for Testing and Methods
BACT	Best Available Control Technology
CAA	federal Clean Air Act
CFR	Code of Federal Regulations
CO	Carbon Monoxide
CO ₂	Carbon Dioxide
District	San Diego County Air Pollution Control District
EF	Emission Factor
EPA	US Environmental Protection Agency
HAP	Hazardous Air Pollutant
I&M	Inspection and Maintenance
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
[NSR]	New Source Review based condition
NO _x	Oxides of nitrogen
O ₂	Oxygen
OES	Office of Environmental Services
O&M	Operation and maintenance
Pb	Lead
PM	Total Particulate Matter
PM ₁₀	Particulate matter with aerodynamic equivalent diameter of ≤ 10 microns
PSD	Prevention of Significant Deterioration
RMP	Risk Management Plan
SDCAPCD	San Diego County Air Pollution Control District
SIP	State Implementation Plan
SO _x	Oxides of sulfur
Title IV	Title IV of the federal Clean Air Act
Title V	Title V of the federal Clean Air Act
VOC	Volatile organic compound
Units of Measure:	
dscf	= Dry standard cubic foot
g	= grams
gal	= gallon
gr/dscf	= Grains per dry standard cubic foot
hr	= hour
lb	= pound
in	= inches
max	= maximum
min	= minute
MM Btu	= Million British thermal units
psia	= pounds per square inch, absolute
scf	= Standard cubic foot
scfm	= standard cubic feet per minute
yr	= year