

SUBPART L - Standards of Performance for Secondary Lead Smelters
(Delegation Effective 11-8-76)

RULE 260.120. APPLICABILITY AND DESIGNATION OF AFFECTED FACILITY

The provisions of this subpart are applicable to the following affected facilities in secondary lead smelters which commenced construction, reconstruction, or modification after June 11, 1973: pot furnaces of more than 250 kg (550 lb) charging capacity, blast (cupola) furnaces, and reverberatory furnaces.

RULE 260.121. DEFINITIONS

As used in this subpart, all terms not defined herein shall have the meaning given them in Subpart A of this Regulation.

- (a) "**Reverberatory Furnace**" includes the following types of reverberatory furnaces: stationary, rotating, rocking, and tilting.
- (b) "**Secondary Lead Smelter**" means any facility producing lead from a lead-bearing scrap material by smelting to the metallic form.
- (c) "**Lead**" means elemental lead or alloys in which the predominant component is lead.

RULE 260.122. STANDARD FOR PARTICULATE MATTER

(a) On and after the date on which the performance test required to be conducted by Rule 260.8 is completed, no owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from a blast (cupola) or reverberatory furnace any gases which:

- (1) Contain particulate matter in excess of 50 mg/dscm (0.022 gr/dscf).
- (2) Exhibit 20 percent opacity or greater.

(b) On and after the date on which the performance test required to be conducted by Rule 260.8 is completed, no owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any pot furnace any gases which exhibit 10 percent opacity or greater.

RULE 260.123. TEST METHOD AND PROCEDURES

Performance tests shall be conducted as specified in Part 60, Chapter I, Title 40, Code of Federal Regulations, Section 60.123.