

**ADHESIVES USAGE LOG
 SAN DIEGO AIR POLLUTION CONTROL DISTRICT
 RULE 67.21 – ADHESIVE MATERIAL APPLICATION OPERATIONS
 (INCLUDES ALL ADHESIVES & COMPONENTS)**

Date	Manufacturer & Manufacturer ID	VOC Content (of material)	VOC Content (Less water & Exempt Compounds)	Mix Ratio	Coating Category Per 67.21(d)(1)	Amount Applied
	Adhesive:					
	Catalyst:					
	Reducer:					
	Other:					
	Adhesive:					
	Catalyst:					
	Reducer:					
	Other:					
	Adhesive:					
	Catalyst:					
	Reducer:					
	Other:					
	Adhesive:					
	Catalyst:					
	Reducer:					
	Other:					

RULE 67.21 ADHESIVE MATERIAL APPLICATION OPERATIONS- GUIDELINES FOR COMPLETING FORM

Column 1: Enter the date.

Column 2: Enter the manufacturer's name and identification for each adhesive and component part used.

Column 3: Enter the Volatile Organic Compound (VOC) content of the material for each adhesive and component part used.

Example: 2.3 lbs/gal (pounds per gallon) or 275 g/l (grams per liter)

Column 4: Enter the Volatile Organic Compound (VOC) content less water and exempt compounds for each adhesive and component part used.

Example: 3.5 lbs/gal (pounds per gallon) or 420 g/l (grams per liter)

Column 5: Enter the mix ratio for each adhesive component.

Column 6: Enter the coating category from Rule 67.21(d)(1). Example- architectural sealant or subfloor adhesive

Column 7: Enter the amount of the adhesive (including all component parts) applied.