

## CALIFORNIA HAZARDOUS WASTE

### GENERATOR SUMMARY CHART

	<b>SQG</b>	<b>LQG</b>
<b>Monthly Generation Quantity Limit for non-acute/non-extremely hazardous waste</b>	< 1,000 kg/month §66262.34(d)	≥ 1000 kg/month §66262.34(a)
<b>Monthly Generation Quantity Limits for acute/extremely hazardous waste</b>	≤ 1 kg/month §66262.34(d)(3)	> 1 kg/month §66262.34(a)
<b>HW determination</b>	§66262.11	§66262.11
<b>EPA ID Number</b>	Required §66262.12	Required §66262.12
<b>On-Site Accumulation Quantity Limits</b>	6000 kg §66262.34(d)(1) 1 kg acute/extremely	No Limits
<b>Accumulation Time Limits for non-acute/non-extremely hazardous waste</b>  <i>California never adopted the CESQG federal regulation 40 CFR 261.5. Generators of &lt;1,000 kg/month are classified as SQGs in California. One exception is accumulation time limit starts for &lt;100 kgs waste.</i>	≤180 days or ≤270 days (if > 200 miles) §66262.34(d)*  If an SQG's quantity of HW generated does not exceed 100 kg in the first or subsequent month, the applicable accumulation time limit above begins when the generator first accumulates 100 kg of HW HSC §25123.3(c)  *Does not include returned wastes 66262.34(g) & (h)	≤90 days §66262.34(a)
<b>Accumulation Time Limits for acute/extremely hazardous waste</b>	≤90 days from the date the 1Kg on-site accumulation quantity limit is reached HSC §25123.3(h)(1)(C)	90 days from the date 1Kg of acutely/extremely hazardous waste is first accumulated HSC §25123.3(c)
<b>Accumulation Time Extensions (for unforeseen, temporary, or uncontrollable circumstances)</b>	For RCRA hazardous waste, a 30-day extension may be granted by DTSC §66262.34(c) 40 CFR 262.34(f)	For RCRA hazardous wastes, a 30-day extension may be granted by DTSC §66262.34(c)

## CALIFORNIA HAZARDOUS WASTE

### GENERATOR SUMMARY CHART

	For non-RCRA hazardous waste, a 90-day extension may be granted by the CUPAs §66262.35	For non-RCRA hazardous waste, a 90-day extension may be granted by the CUPAs §66262.35
<b>Storage Requirements</b>	Basic requirements with technical standards for containers and tanks 40 CFR 262.34(d)(2),(3) & (4)	Full compliance for management of tanks, containers, drip pads, or containment buildings §66262.34(a)(1)
<b>Use and Management of Containers</b>	40CFR 265.171 - .177, except .176 & .178	§66265.171-.178
<b><i>Container Marking/Labeling</i></b>	Required §66262.34(f) Label as “Hazardous waste” w/start date, and include additional information (i.e., physical composition, hazard properties, name and address of generator)	Required §66262.34(f) Label as “Hazardous waste” w/start date, and include additional information (i.e., physical composition, hazard properties, name and address of generator)
<b><i>Marking/Labeling Returned wastes</i></b>	Required §66262.34(h)	Required §66262.34(h)
<b><i>Closed Container Requirement</i></b>	Closed except when adding/removing wastes 40CFR 265.173(a)	Closed except when adding/removing wastes §66265.173(a)
<b><i>Container Condition</i></b>	Free of severe rust, major dents, leakage. 40CFR 265.171	Free of severe rust, major dents, leakage. §66265.171
<b><i>Compatibility of wastes w/Container</i></b>	Required 40CFR 265.172 Container compatible with waste placed in it.	Required §66265.172 Container compatible with waste placed in it.
<b><i>Container Inspection</i></b>	Required 40CFR 265.174 Must inspect weekly (no written logs required)	Required §66265.174 Must inspect weekly (no written logs required)
<b><i>Special container requirements for storing</i></b>	None	Container must be located ≥50 feet from property line

## CALIFORNIA HAZARDOUS WASTE

### GENERATOR SUMMARY CHART

<b><i>Ignitable /Reactive Wastes</i></b>		§66265.176
<b><i>Special container requirements for storing incompatible wastes</i></b>	Required 40 CFR 265.177 Incompatibles <u>must not</u> (1) be placed in same container, (2) must not be place in unwashed container that previously held an incompatible waste, and (3) must be properly separated from other incompatible wastes (e.g., by dike, berm)	Required §66265.177 Incompatibles <u>must not</u> (1) be placed in same container, (2) must not be place in unwashed container that previously held an incompatible waste, and (3) must be properly separated from other incompatible wastes (e.g., by dike, berm)
<b><i>Subpart CC Air Emissions for Containers</i></b>	Not required	Required §66265.1087 Applies if >26 gallons and holds a VOC containing waste of >500 ppm. Must accumulate in tightly closed DOT container only.  Does not include containers in Satellite Accumulation Areas (§66265.1080(a)/66265.1)
<b><i>Container Aisle Space</i></b>	Required 40CFR 265.35 Must leave enough room for unimpeded access to container	Required §66265.35 Must leave enough room for unimpeded access to container
<b><i>Satellite Accumulation (Point of Generation)</i></b>	Up to 55 gallons (or 1 qt. acutely or extremely HW) per waste stream, at or near point of generation, under control of operator, mark with 2nd (fill) date once full. Accumulate for up to 1 year total or 180 days from fill date, whichever is first. §66262.34(e) ALSO: HSC 25200.3.1 (laboratories)	Up to 55 gallons (or 1 qt. acutely or extremely HW) per waste stream, at or near point of generation, under control of operator, mark with 2nd (fill) date once full. Accumulate for up to 1 year total or 180 days from fill date, whichever is first. §66262.34(e) ALSO: HSC 25200.3.1 (laboratories)
<b><i>Empty containers (&gt; 5 gallons)</i></b>	Mark with date emptied & manage within 1 year unless returned to vendor for refill §66261.7(e), (f) & (i)	Mark with date emptied & manage within 1 year unless returned to vendor for refill §66261.7(e), (f) & (i)

## CALIFORNIA HAZARDOUS WASTE

### GENERATOR SUMMARY CHART

<b>Tank Management</b>	40CFR 265.201	§66265.190-.202, except for .197(c) & .200
<b><i>Tank Marking</i></b>	Required §66262.34(f) Label as “Hazardous waste” w/start date, and include additional information (i.e., physical composition, hazard properties, name and address of generator)	Required §66262.34(f) Label as “Hazardous waste” w/start date, and include additional information (i.e., physical composition, hazard properties, name and address of generator)
<b><i>Marking/Labeling Returned wastes</i></b>	Required §66262.34(h)	Required §66262.34(h)
<b><i>Tank System Integrity Assessment</i></b>	Not required	Required § 66265.191/192(a) § 66265.193(i)(2) Frequency and contents of assessment dependent upon waste and installation date of tank.
<b><i>Tank System Secondary Containment &amp; Leak Detection</i></b>	Not required	Required § 66265.193 § 66265.193(m)(2)(A) Some aboveground piping/ancillary equipment may be exempt if inspected daily.
<b><i>Tank Operation/Spill Prevention</i></b>	Some controls required. 40CFR 265.201(b)(2) & (3) Must keep 2’ freeboard on open top tanks unless in containment with volume to hold those 2’. If continuously fed tank must have measures to prevent overflow (e.g. waste cutoff or diversion tank).	Controls required §66265.194 Spill prevention (e.g. check valves), overflow prevention (e.g. high level alarms), and for uncovered tanks maintenance of freeboard of 2 feet unless the tank is equipped with containment structure.
<b><i>Tank Inspection</i></b>	No written logs required 40CFR 265.201(c) Daily inspection of discharge controls (e.g. bypass systems), monitoring data, and level in tank. Weekly inspection of tank	Required daily. §66265.195 Written logs required.

## CALIFORNIA HAZARDOUS WASTE

### GENERATOR SUMMARY CHART

	and containment for leaks.	
<b><i>Tank Release Response</i></b>	Not required	Required §66265.196 Within 24 hours must drain tank to level to prevent further release, clean up all waste in containment, report to DTSC (unless <1lb or immediately cleaned up)
<b><i>Subpart CC Air Emission Standards for Tanks</i></b>	Not required	Required 66265.1085(c) -Tank <19,000 gal, holds VOC >500 ppm (by weight) needs fixed roof §§66265.1083(b) & -Tank holding VOCs that does not meet criteria above, has cover and control/closure devices §66265.1085(d)
<b>Contingency Plan</b>	Basic plan only. 40 CFR 262.34(d)(5)(i) & (ii) Must post info near phone -Name & number of emergency coordinator -Location of emergency equipment -911 or local fire department number	Full plan required. §66265.51-.54 Must review and update with any relevant change. Must include OES phone #, name and office and home phone #s of contacts, all emergency equipment (capabilities and location), and evacuation plan.
<b>Emergency Procedures</b>	Required 40 CFR 262.34(d)(5)(iv)	Required §66265.55 -.56
<b><i>Activation/ Notification</i></b>	Notify National Response Center at 800-424-8802 40CFR 262.34(d)(5)(iv)(C)	Immediately notify; Within 15 days, notify in writing of any incident that activates plan §66265.56(a) and §66265.56(d) & (j)
<b>Preparedness and Prevention</b>	Required 40 CFR 265.30 - .37	Required §66265.30 - .37

## CALIFORNIA HAZARDOUS WASTE

### GENERATOR SUMMARY CHART

<b><i>Emergency Equipment</i></b>	Must have internal communications device, external communication device (phone), fire extinguishers, spill control and decon equipment. 40CFR 265.32	Must have internal communications device, external communication device (phone), fire extinguishers, spill control and decon equipment. §66265.32
<b><i>Inspection/Maintenance</i></b>	Tested and maintained as necessary to respond to emergency 40CFR 265.33	Develop schedule for inspection of all emergency equipment. Maintain written logs of inspections with any corrections. and 66265.33
<b><i>Facility Maintenance</i></b>	Maintained and operated to minimize possibility of release, fire or explosion 40CFR 265.31	Maintained and operated to minimize possibility of release, fire or explosion §66265.31
<b>Personnel Training</b>	Basic training required 40 CFR 262.34(d)(5)(iii)	Required §66265.16
<b><i>Training Plan</i></b>	Not required	Written plan required §66265.16(a) & (d) Includes: job titles or HW related positions, description of each job title (including duties), name of each person at each job title, type and frequency of training
<b><i>Training Records</i></b>	Not required	Required §66265.16(d) & (e) Maintain documentation of initial and ongoing for current employees until facility closure. Former employee records maintained for 3yrs from date of last work.
<b><i>Frequency of Training</i></b>	Not required	Within 6 months of hire, at frequency noted in plan, annually for emergency response §66265.16(c)
<b>Manifest and Consolidated Manifest</b>	Required §66262.20  Consolidated manifesting for select wastes. HSC 25160.2	Required §66262.20  Consolidated manifesting may be used for select wastes <b>IF</b> the facility is an LQG who

## CALIFORNIA HAZARDOUS WASTE

### GENERATOR SUMMARY CHART

		qualifies when they perform a count for the purposes of “consolidated manifesting. (i.e., subtracting the amount of used oil from its total monthly) quantity limits. HSC 25160.2(c)(1, 2)
<b>Off-site Management of Waste</b>	Must send to a state approved or RCRA permitted/interim status facility §66262.20(b)	Must send to a state approved or RCRA permitted/interim status facility §66262.20(b)
<b>Biennial Report</b>	Not required	Required §66262.41 Submit by March 1 every even numbered year for prior 2 years activities. Maintain onsite. RCRA LQGs only.
<b>Recordkeeping Requirements</b>		
<b><i>Manifest Submittal to DTSC</i></b>	Required §66262.21(f) Generator submits legible photocopy to DTSC See also HSC 25160(a)(3)	Required §66262.21(f) Generator submit legible photocopy to DTSC See also HSC 25160(a)(3)
<b><i>Land Disposal Restrictions (LDRs)</i></b>	Required §66268.7; HSC §25179.5	Required §66268.7; HSC §25179.5
<b><i>Manifest Exception Reports</i></b>	Required §66262.42(c) File report noting no receipt of TSDf copy if not received within 60 days	Required §66262.42(b) File report noting no receipt of TSDf copy if not received within 45 days
<b>DOT Transport Requirements</b>	Yes §§66262.30-66262.33	Yes §§66262.30-66262.33
<b>Generator closure</b>	Tank cleaning 67383.3	Required 66265.111 & .114 and 67383.3